

ORDER FORM

HAND ORTHOSIS

1. Company address/Company stamp

Phone

Date

Commission

E-Mail (Confirmation of receipt and tracking number)

Responsible staff

Signature

2. User details

Has been pre-supplied with a product of ours: yes no **If „yes“** _____
S.-Nr./Date

Date of birth

Version: a pair only left only right

Activity level: 1 2 3 4

Diagnosis:

Additional input:

Important Notes:

1. Together with the completed order form we need a rectified and **smooth** plaster positive. Alternatively send a rectified CAD-file to 3d@casimo-ot.de.
 A draped check-orthosis to define trim lines and velcro strap positions supports a perfectly fitting device.
2. Please mark the position and the trim lines with a permanent marker on plastic or with a **lead pencil** on plaster.
3. **No** modelled edge!

ORDER FORM

HAND ORTHOSIS

3. Orthosis version

- HTV-hand orthosis short
 HTV-hand orthosis long (covering the wrist)

4. Execution details:

Silicon color: _____ (casimo colors, please see casimo-ot.de)
 _____ (Ral-color)

Velcro straps color:
 grey
 black
 blue
 orange
 red
 skin
 yellow
 green
 white

Velcro strap width:
 20mm
 30mm
 50mm
 (please set position via drawing)

Individual Design: _____

Closure technique:

<input checked="" type="radio"/> standard	<input checked="" type="radio"/> user defined	<input checked="" type="radio"/> closed
<input type="radio"/> orthosis with closure cover <input type="radio"/> velcro <input type="radio"/> loop on both sides	<input type="radio"/> orthosis with closure cover <input type="radio"/> without loop	<input type="radio"/> fully closed <input type="radio"/> half closed

Shore hardness* orthosis:

<input checked="" type="radio"/> standard	<input checked="" type="radio"/> user defined
50° in 3mm	<input type="radio"/> 20° <input type="radio"/> 35° <input type="radio"/> 50° <input type="radio"/> 65° <input type="radio"/> 80° mm
65° in 2mm	<input type="radio"/> 65° ____ mm <input type="radio"/> 80° ____ mm <input type="radio"/> Prepreg

shore hardness orthosis
 reinforcement
 reinforcements according to your drawings

[* 20° = very soft | 35° = soft | 50° = medium | 65° = hard | 80° = very hard]